

Main range	Thalassa
Category	Enclosure
Version	PLD
enclosure type	DIN enclosure
	Distribution enclosure
Nominal height	850 mm
Nominal width	465 mm
Nominal depth	320 mm
enclosure mounting	Floor-standing
product compatibility	Fuse 00
Complementary device composition	1 top part 1 bottom part 2 side part 1 rear panel 1 key lock 1 door
body type	Sealed top and open bottom part assembled with side parts
door type	Plain front
number of doors	1 door(s)
door opening side	Reversible (180 °)
lock type	Key lock
key number	1242 E
accessibility for operation	Front Bottom
removable parts	Door by hinges
material	Polyester reinforced with fibreglass
colour	Grey (RAL 7035)
Environment standards	IEC 62208

IP degree of protection

IP43 conforming to IEC 60529 (plinth type open bottom)

IP54 conforming to IEC 60529 (with additional sealing kit)

IK degree of protection

IK10 conforming to IEC 62262 (plain door)

fire resistance

960 °C conforming to IEC 62208

ambient air temperature for storage

-35...90 °C

Offer Sustainability

Sustainable offer status

Green Premium product

REACH Regulation

[REACH Declaration](#)

EU RoHS Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

Mercury free

Yes

RoHS exemption information

[Yes](#)

China RoHS Regulation

[China RoHS declaration](#)

Product out of China RoHS scope.
Substance declaration for your information

**Environmental
Disclosure**

[Product Environmental Profile](#)

Circularity Profile

No need of specific recycling operations